

High Court of Judicature of Allahabad

Quotation for supply of Line Matrix Printers

Sealed quotations are invited from the reputed firms/O.E.M. dealing with heavy duty Line Matrix Printers, for High Court, Allahabad.

The interested firm/O.E.M. must submit their quotation in attached proforma (General information/Technical Specification) latest by **15th December, 2011 upto 4.00 p.m.** positively at Computer Centre, High Court, Allahabad with Earnest Money of Rs.15,000/- through Demand Draft in favour of Registrar General, High Court, Allahabad. The quotations received shall be opened on the same day at 4.30 p.m. in the Computer Centre in the presence of firms/O.E.M. (*Max. 2 person allowed from each firm.O.E.M.*) who wish to remain present at that time.

**Sd/-
Registrar General**

High Court of Judicature of Allahabad
Supply of Line Matrix Printer

General Information

1.	Name of the firm	
2.	Full address of firm along with Contact Person Telephone no. Fax no. E-mail address:	
3.	Trade Tax / Sales Tax Registration no. with place	
4.	Income Tax Registration no. with place	
5.	Kindly mention and enclose at least two supply Order copy from your customers where you have supplied Line Matrix Printers.	
6.	Name & Model of the product quoted (Separate sheets may be used if required)	
7.	Any other information you feel necessary (Separate sheets may be used if required)	
8.	Details of earnest money attached. (i) Amount Rs. (ii) Bank Draft No. (iii) Bank Draft issuing date (iv) Drawn on (Bank)	Rs.15,000/-
9.	Warranty period after refilling	
10.	Details of refilling	

High Court of Judicature of Allahabad

Technical Specification of Line Matrix Printers

Parameter	Specification	
Print Method	Impact Line Matrix	
Print Speed	Print Speed (LPM, upper case characters, lower case characters) :- High Speed – 1200/1500 Graphics Speed :- 60 x 72 dpi – 100 inches per minute	
Typefaces	High Speed, Data Processing, Near Letter Quality	
Character Pitch	10,12,13.3,15,17.1,20	
Line Spacing	6,8,10.3,n/72,n/216	
Minimum Resolution	180 dpi(H) x 144 dpi(V)	
Printable Width	2.5" to 18.9"	
Emulations	Serial matrix printer, Epson FX 1800, IBM ProPrinter III XL, Printronix P Series, Printronix P Series XQ, DEC LG, ANSI 3.64	
Resident Character Sets	Unicode UTF-8, IBM World Trade, ECMA Latin-1, DEC Multinational, IBM Code Page 437 and 850, OCR A, OCR B	
Fonts	High Speed, Data Processing, Serif, Sans Serif, OCR-A, OCR-B	
Character Styles	Bold, italic, superscript, subscript, underline, overstrike, strike through	
Bar Codes	Code 39, Code 128, interleaved 2/5, UPC-A,UPC-E, EAN 8, EAN 13, EAN 128, Codabar, Identicon 2 to 5, MSI, POSTNET, Royal Mail, PDF 417	
Paper Handling	Type	Fan folded, Continuous, Edge-perforation
	Width	3" to 17"
	Copies	Upto 6 parts
	Thickness	0.025"
	Paper Path	Straight through paper path with easy-load dual adjustable tractors
	Feed	Bottom feed
	Forms Control	14 & 12 channel electronic vertical format unit, paper-out detector and alarm, paper motion detector and alarm.
Interface	IEEE-1284 Parallel Port, RS-232, Ethernet 10/100 and Wireless 802.11b/g.	
Ribbon	With text application, bar code and OCR – 90 million characters capacity.	
Acoustic Noise	55dB	
Driver Availability	Linux, Windows 98/NT/2000/ME/XP	
Electrical Specification	Input Voltage	150-270VAC
	Frequency	47 Hz – 60 Hz
Enclosure	Enclosed Cabinet with aesthetically pleasing colour and texture. The enclosure must have slide out paper trays.	
Warranty	3 years comprehensive on-site warranty.	